

Product technical data sheet

GUILBERT EXPRESS
Le Pérípole, Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
94127 Fontenay sous Bois Cedex
Tel: +33 (0)825 800 251 - Fax: +33 (0)825 800 238

LAC - 525 - 531 - 511	
Created on	31/03/2005
Modified on	27/09/2017
Issue	C

Cat. No. **525 - 531 - 511**
Name: **LAC GP**

Product: Cartridge blowlamp
Job: Multi-application
Users: General public
Energy: Gas

Description

Interchangeable burner.
Hanging ring.
Grip for improved handling.
Accurate gas flow control.
Adjustable stabilizer stand.
Attractive plastic casing.

Areas of application

Plumbing, welding, brazing, flame cleaning,
unjamming, burning, defrosting.



Content of products

	531	525	511
Gas cartridge 555	X		X
Gas cartridge 2015		X	
Sharp-tip flame	X	X	X
Cerco flame	X	X	
Flat flame	X		

Technical data

	Sharp-tip	Cerco	Flat
Flow rate (g/hr) according to French standard NF EN 521	100		
Power (kW) according to French standard NF EN 521	1,4		
Flame temperature (°C)	1200 to 1850	equivalent to 2400	1850
Copper pipe brazing capacity with CuPh (mm)	555	Ø14	No
	2015	Ø18	Ø20
Approximate operating time (hr)	2		

Spare parts

3555	Cercolamp with enveloping flame
3550	Flat-flame burner
3542	Sharp-tip-flame burner

Packaging

	Weight (g)	Width (mm)	Depth (mm)	Height (mm)
Tool in plastic casing Cat. No. 525	829	165	75	410
Tool in plastic casing Cat. No. 531	875	165	75	410
Tool in plastic casing Cat. No. 511	740	165	75	410
Extra packaging Cat. No. 531 (96 parts)	84000	800	600	600
Extra packaging Cat. No. 525 (96 parts)	79584	800	600	600
Extra packaging Cat. No. 511 (96 parts)	71040	800	600	600
Sales unit: 2 parts				

Other

All of these products are compatible with both gas cartridges: Cat. No. 555 and Cat. No. 2015.

IMPORTANT: Read instructions before use - For use only in sufficiently well ventilated rooms.

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs

www.express.fr