

Product Technical Data

GUILBERT EXPRESS
 Le Pérípole, Lot 209-210
 33 avenue du Maréchal de Lattre de Tassigny
 F-94127 Fontenay sous Bois Cedex
 Tel.: + 33 1 53 99 16 98 - Fax : + 33 1 53 99 16 56

Lamp'piezo 351	
Created on	26/10/2001
Modified on	12/02/2018
Issue	L

Ref.: 351
Name: Lamp' Piezo

Product: Cartridge blowlamp
Activity: Plumbing, Air conditioning
User: Professionals
Energy: Butane / Propane gas

Description - Ref. 351

1 cartridge lamp head
 1 butane-propane-propylene cartridge Ref. 2015
 in cardboard box

Application fields

Plumbing, tin soldering, brazing, loosening of nuts and bolts, burning.

Flame type: Sharp tip
Flame dimensions: Dia. 20 mm x 60 mm
Nozzle inner diameter: Dia. 18 mm



Functions

On/Off and gas flow control	Yes	Knob
Flame adjustment	Yes	Knob
Piezo ignition	Yes	Button
Immediate flip over	Yes	5 s max. (10 s when cartridge is used for the first time)
Foot	Yes	Rotating

Technical features as per gas

pressure (bar / PSI)
 Gas flow (g/h)
 Power (kW)
Power (BTU/h)
 Autonomy (hours)

555	2015	2400
3 b / 44 PSI	4 b / 58 PSI	7 b / 102 PSI
129	143	214
1,8	2	2,9
6030	6680	9930
1h40	1h20	1h50

Soldering capacity on straight union Ømm as per gas

With CuPh solder
 With 6% Ag solder

555	2015	2400
Ø 18	Ø 20	22
Ø 18	Ø 22	22

Interface

Connection to gas cartridges Ref. 2015 and 555 and to Mapp © cylinder with union Ref. 905

Accessories:

Mapp© union Ref. 905
 Set of 10 O-rings for cartridge lamp head Ref. 35563

Main materials

Nozzle Stainless steel
 Valve Brass
 Burner Brass

Packaging

	Weight (g)	Width (mm)	Depth (mm)	Height (mm)
Appliance in cardboard box - Ref. 351	800	105	70	315
Appliance in cardboard box - Ref. 353	850	105	70	315

IMPORTANT: Read instructions before use - Use only in well ventilated areas.

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Non-contractual photos.