

GUILBERT EXPRESS Le Péripole, Lot 209-210 33 avenue du Maréchal de Lattre de Tassigny 94127 Fontenay sous Bois Cedex - France Tel.: + 33 1 53 99 16 98 - Fax : + 33 1 53 99 16 56

Product Technical Data

Sharp tip flame burners				
Created on	19/06/03			
Modified on	06/03/12			
Issue	Α			

Ref.: 4641 / 4642 / 4643 / 4651 4541 / 4542 / 4543 / 4551

Name: Sharp tip flame burners

Product: Burner

Activity: Plumbing, copper tube

User: Professionals / General public

Engergy: GAS

Description

Aerosol gas burners, sharp tip flame.

For all application fields: hard and soft soldering, heating, shrinking, forming, etc.

Gas supply from 1 to 4 bar (butane or propane).

Flame temperature adjustment from 1200 to 1850°C by means of the air ring.

Total versatility using a pressure regulator type 686 or 694.

Very fine adjustment.



Technical features	4541 / 4641		4542 / 4642		4543 / 4643		4551 / 4651	
Pressure (in bar)	2	4	2	4	2	4	2	4
Flow (in g/h)	23	39	128	213	287	479	441	734
Power (in kW)	0.32	0.54	1.77	2.94	3.96	6.61	6.09	10.13
Weight (in a)	95	1	10	2.4	1	127 g	10	63.2

Soldering capacity (for information)

Copper tube dia., with CuPh, at 3 bar 6 14 23 32

Spare parts

 Gas outlet Ref.
 15104
 9234
 15304
 4622

 Swaged nozzle Ref.
 15109
 15209
 15309
 15409

 Air ring Ref.
 5766
 5766
 5766
 5758

Miscellaneous

Nozzle inner dia. (in mm) 11.5 13 17 19

Packaging	4541	4641	4542	4642	4543	4643	4551	4651
Weight (in g)	116	94	134	113	150	140	190	170
Type	Р	S4	Р	S4	Р	S4	Р	S4

Associated EXPRESS products

Professional handles Ref. 600
Ref. 602
Ref. 605
Ref. 606
Ref. 620
Ref. 620
Ref. 640

Packaging images (example)

P = Skin pack on cardback: (100 × 290) S4 = Plastic bag with burner hook: (180 × 250)





S4

Regulation

Designed as per: EN731 Burners to be used only with EXPRESS handles.