

# Product datasheet

**GUILBERT EXPRESS**

Le Péripole, Lot 209-210  
33 avenue du Maréchal de Lattre de Tassigny  
94127 Fontenay sous Bois Cedex  
Tel: +33 (0)825 800 251 - Fax: +33 (0)825 800 238

Cat. No.: 460	
Created on:	08/06/2020
Modified on:	08/06/2020
Issue:	A

**Description**

Piezo ignition  
Flow rate controlled by regulator  
Can be pointed downward instantly  
Hanging ring  
Accurate gas flow control  
Removable stabilizer stand  
Attractive plastic casing  
Handle with safety cut-off  
MAPP and propane gas compatible  
Continuous or trigger-controlled flame

**Areas of application**

Plumbing, welding, brazing, flame cleaning, unjamming, burning, defrosting.

Vulcane ONE weight: 375 g  
Weight in packaging on hang tab: 450 g



**Technical data**

Gas	Pressure		Consumption	Power		For tube	"Turbo" type flame		
	Type	bar		psi	g/h		kW	BTU/h	Cu Ø (mm)
XPRESS 2400		1.4	20	204	2.7	9200	10 - 22	18	80
Propane		1.4	20	227	3.1	10690	10 - 22	18	80

**Spare parts**

Designation	Cat. No.
100% propylene cylinder	2400
Stabiliser stand	4702
Extension hose	4770

2400



4770

4702



**IMPORTANT: Read instructions before use**

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs

[www.guilbert-express.net](http://www.guilbert-express.net)