

**Product:** Hot Air gun  
**Activity:** Heat Shrink Tubing  
**User:** Professional  
**Energy:** Cartridge Cat. No. 445

**Cat. No. 4600 Description**

- Composition :**
  - 1 complete gun
  - 1 Gas cartridge Cat. No. 445
  - 1 Flat nozzle
  - 1 Nozzle with deflector
  - 1 Stand for hand free use
  - 1 Protective cover
  - 1 Technical notice
  - Delivered in a case
- Functions :**
  - Ignition
  - Instant turnaround
  - Flow ajustement
  - Autonomy > 1h30
  - Temperature from 190 °C / 400 °F to 900 °C / 1650 °F
- Advantages :**
  - Autonomy
  - Lightweight
  - Handy
  - Stable
- Maintenance :**
  - Tirigger + piezo can be changed without tool
  - Injector can be changed without tool



**Data sheet**

Cartridges Cat. No.	444 - 445
Gas flow (g/h)	38
Power (W)	520
Power (BTU/h)	1700
Temperatures (°F)	392 -> 1382
Device Mass without cartridge (g)	450

**Nozzle outlet temperature**

Distance (Wall - Nozzle end)	Cartridge	2 cm	4 cm	6 cm	8 cm
Temperature without nozzle (°C/°F)	445	900/1650	660/1200	580/1100	420/800
Temperature flat nozzle (°C/°F)	445	740/1350	470/900	380/700	420/800
Temperature without nozzle (°C/°F)	444	800/14750	620/1150	530/1000	230/450
Temperature flat nozzle (°C/°F)	444	700/1300	460/850	370/700	190/400
Nozzle with deflector	Tin soldering copper tube up to Ø 32 mm				

**Accessories**

	Cat. No.
Protective cover	39193
Stand	4702
Flat nozzle	11965
Nozzle with deflector	11255

**Spare parts**

	Cat. No.
Trigger/piezo	39191
Burner with injector	39194
Injector	39192

**Conditioning**

Cat. No. 4600	Case	Mass (g)	Width (mm)	Depth (mm)	Height (mm)
		1370	310	110	290

**IMPORTANT: Read instructions before use - For use only in sufficiently well ventilated rooms.**

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Products may differ from photographs.